



Type Approval Certificate

[Cryogenic Top entry ball valve]

Initial Approval 20 July 2021

Manufacturer BMT Co., Ltd.

17 Sinsojaesandan 2-ro, Jangan-eup, Gijang-gun, Busan, 46031, Republic of Korea

Product Description Cryogenic Top-Entry Ball Valve

- Model : FCBT1 Series

- Intended for : Liquid and Gas Service

“ See Appendix 1 ”

Approval Condition

“ See Appendix 1 ”

THIS IS TO CERTIFY that the above-mentioned product has been approved in accordance with the relevant requirement of this Society's Rules and / or of the recognized standards as follows.

Pt. 7, Ch. 5, Art. 513 of the Rules for Classification, Steel Ships and IGC Code, ASME B16.34, B16.10, B16.25 & BS6364

This Certificate is valid until 19 July 2026

Reissued at Busan, Korea on 21 February 2024



This certificate is signed electronically in accordance with IMO FAL.5/Circ.39/Rev.2. Validation and authentication of the certificate can be confirmed from "<http://e-cert.krs.co.kr>" by using the tracking No(ME24008078737) and certificate No.(CSP35101-VV018).



KOREAN REGISTER

*General Manager of
Marine & Ocean Equipment Team*

- Note :**
1. This certificate will be valid subject to complying with the approval conditions described on the certificate and/or on the Rules of this Society.
 2. This certificate will be invalid from the expiry date aforementioned unless the extension or renewal has been granted to the applicant or the manufacturer.
 3. Any significant modifications or changes in design or construction to the above product without approval from this Society will render this certificate invalid.
 4. Should the specified rules, regulations or standards be amended during the validity of this certificate, the product is to be re-approved by this Society in accordance with the requirements as amended.

Product Description and/or Approval Condition

Date of Issue : 21 February 2024

A. Product Description

1. Product Specification

- 1) Model : FCBT1 Series
 - Design Temp. : -196°C to +100°C
 - Pressure Class : ANSI Class 150
 - Size : 3", 4", 6", 8", 10", 12"
 - Design Pressure : 19 bar at 38°C
 - End Connection : RF, BW
 - Material
 - Shell : ASTM A351 CF8M
 - Stem : ASTM A276-316

2. Approved Drawings and Documents

- 1) 200810-01-119-01, 200810-01-119-02 dated on 15 December 2020.
- 2) 190725-115-01 dated on 01 April 2020.
- 3) CBT1CARF1-48-BY, CBT1CA-48-BT, CBT1CA-48-BL, CBT1CA-48-SM dated on 13 May 2020.
- 4) CBT1CARF1-64-BY, CBT1CA-64-BT, CBT1CA-64-BL, CBT1CA-64-SM dated on 30 April 2020.
- 5) CBT1CARF1-128-BY, CBT1CA-128-BT, CBT1CA-128-BL, CBT1CA-128-SM dated on 20 April 2020.
- 6) CBT1CARF1-160-BY, CBT1CA-160-BT, CBT1CA-160-BL, CBT1CA-160-SM dated on 17 March 2020.
- 7) CBT1CARF1-192-BY, CBT1CA-192-BT, CBT1CA-192-BL, CBT1CA-192-SM dated on 27 April 2020.

3. Test Reports, etc.

- 1) BMT-CTR-201202-TA-01 (Size 6") dated on 02 December 2020.
- 2) BMT-CTR-210513-TA-06, 7 (Size 3", 4") dated on 14 May 2021.
- 3) BMT-CTR-210716-TA-01, 2, 3 (Size 8", 10", 12") dated on 19 July 2021.

B. Approval Condition

1. Application & Limitation

- 1) The materials used for valve body & etc. as appropriately are to be certified by this Society or to be satisfactory to the Surveyor.
- 2) Gaskets and packings are to be suitable for the condition of use and to have a construction specified in Korean Industrial Standards or equivalent construction thereto.

2. Individual Product Cert. and Drawing Approval Requirement

- 1) Individual Product Certification is required.
- 2) The minimum average energy for Charpy V-notch impact test should be complied with the relevant requirements of the Rules, Pt. 7, Ch. 5.
- 3) The following tests are to be applicable for each size of the valves as individual product certification.
 - Hydrostatic test of the valve body at a pressure equal to 1.5 times the design pressure
 - Cryogenic testing consisting of valve operation and leakage verification for a minimum of 10% of each type and size of valve for valves
 - Proving testing at ambient temperature consisting of leakage test at a pressure equal to 1.1 times the design pressure

3. Marking

- The product is to be permanently marked with manufacturer name and type designation on a suitable position.

4. Others

- N/A

< End of Certificate >